

NEED TO
GENERATE
A MORE
EFFICIENT
WORK FLOW?



Designed to fit your environment

Designed to deliver integrated network printing, scanning and digital copying with more productivity features than any other system in its class.

8825 DDS - simplify your work processes and improve productivity.

- Handles network printing and copy jobs simultaneously
- Ability to scan to file whilst network printing
- Higher throughput than any competitor product in its class
- User-friendly copier control panel
- Preset modes for line, blueprint, and photo originals
- 1 or 2 roll capacity, A4-A0 size
- Job recall and electronic collation
- Auto reduction/enlargement
- Easy, flexible system integration
- Full suite of client software drivers

Expands with your needs

- Optional Scan-to-Net
- Optional Account Data Tracking
- Optional Adobe PostScript 3 for enhanced reliability
- Optional finishing - Folder and Stacker 1000

Xerox Engineering Systems

UK

Tel: 01635 517200 Fax: 01635 517216

OTHER COUNTRIES

Tel: 44 (0) 1635 517322 Fax: 44 (0) 1635 517392

**Come visit us on the
World Wide Web.**

www.XES.com

Your nearest XES representative is:

The XES 8825 Digital Document System Specifications

Printer

Process/Imaging	Xerographic LED
Photoreceptor	Organic
Media Supply	1 roll, 175 m Optional - 2nd Roll; manual sheet bypass
Media Type	Bond, Tracing Paper, Film
Output Size	Min 210 mm x 297 mm Max 914 mm x 24 m (print) Max 914 mm x 30 m (copy)
Resolution	400 dpi
Process Speed	3 ips
Throughput	Up to 4 A1 / 2 A0 per minute
Power Requirements	50 Hz: 240 V: 10 A
Weight	Approx. 250 kgs
Dimensions	1092 mm H x 1446 mm W x 584 mm D
Finishing	Standard - Catch Tray - 50 A0 / 100 A1; Optional - Stacker 1000 - up to 1000 mixed size prints; online Folder

AccXES™ Controller

CPU	Power PC 740
Memory	64 Mb standard; expandable up to 192 Mb
Hard Disk	Standard - 4.5 Gb Ultra SCSI, 7200 rpm, internal drive
Data Formats	HP-GL; HP-GL/2; HP-RTL; CGM (Level 1 with ATA ext.); C4; FileNET; Versatec Data Standards (VRF, ordered vector, blocked raster, compacted raster); CalComp 906/907/951/PCI; TIFF 6.0; NIRS; CALS 1 & 2; compression types (for applicable raster formats): CCITT G4, G3-1D, G3-2D, Packbits, RLE, Seed Row, Adaptive; Optional Adobe Postscript 3
Interfaces	Standard - Serial RS-232; IEEE 1284 Bidirectional Centronics; SCSI-2; VPI; 10/100 Ethernet (TCP/IP) supports 10/100 BaseT Optional - 10 mbs Network Interface Card supports 10 BaseT and 10 Base2
Network Protocols	Standard - TCP/IP with lpr/lpd Optional- Novell IPX/SPX Pserver 3.1/4.1 with NDS; Ethertalk; NetBEUI
Client Software	ADI drivers for AutoCAD R12/13/14 Print Drivers for Win 95/98/NT Web Print Manager Tool for Win 95/98/NT/Solaris Document Submission Tool for Win 95/98/NT Document Retrieval Tool for Win 95/98/NT/Solaris Optional - Adobe PostScript 3 Drivers for Windows 95/98/NT

Scanner

Resolution	400 dpi
Copy/Scan Speed	2 ips at 400 dpi (copy and scan) 2.67 ips at 300 dpi (scan) 4 ips at 200 dpi (scan)
Input	Min 114 mm x 140 mm Max 1041 mm x 30 mm (will only capture 914 mm of image)
Edge / Centre Adjustment	Lead and trail edge adjust / centre alignment
Scan-to-Net	Optional - indexing; scan preview; link to raster editor; resolution selection; TIFF 6.0 data format; TCP/IP Ethernet interface
Power Requirements	50 Hz: 240 V: 10 A

Copier

Reduction/Enlargement	25 to 400% in 0.1% increments
Output Selection	Auto/Manual Roll Selection and Scaling
Concurrency	Scanning/Copying/Printing; Printer Interrupt Key
Digital Retention	Up to 999 copies from a set of 100 standard A0 size drawings
Sets Build	Electronic Collation; Forward; Reverse; Last Scan Replacement; Rescale and Reprint without Rescanning; 999 copies from a set of 100 standard A0 size drawings.
Imaging	Inverse; Mirror; Rotation; 7 copy contrast levels
Auto IQ	Automatic Background suppression / Width detection of original
Copy Modes	Line; Mixed; Photo

Features

Auto port sensing; Auto data format recognition; Auto scaling; Auto rotation; Auto size detection; Auto roll select and switch; Remote printer administration; Prioritised job queuing; Remote job queue management; Electronic collation; 9 pen palettes (256 pens each); 64 pen patterns, including 15 user-definable patterns; Plot labelling with automatic naming and time/date generation; Banner pages; Page composition / plot overlay; Plot stamping with user-downloadable stamps; 10 user setups; 33 grey scales; Media mismatch management; Plot nesting; Control panel lockout

Options

Additional SDRAM Modules in 64 Mb Increments; Stacker 1000; Online Folder; Adobe PostScript 3; 10 mbs Network Interface Card (supports IPX/SPX, NetBEUI and Ethertalk); Manual Sheet Bypass; 2nd Media Roll; Account Data Tracking; Scan-to-Net